

**MATEMATYKA  
DYSKRETNA**

[www.ii.uj.edu.pl/preMD/](http://www.ii.uj.edu.pl/preMD/)

Sylwia CICHACZ, Agnieszka GÖRLICH  
and Zsolt TUZA

*Cordial labeling of hypertrees*

Preprint Nr MD 059  
(otrzymany dnia 2.06.2012)

**Kraków  
2012**

Redaktorami serii preprintów Matematyka Dyskretna są:  
Wit FORYŚ (Instytut Informatyki UJ)  
oraz  
Mariusz WOŹNIAK (Katedra Matematyki Dyskretnej AGH)

# Cordial labeling of hypertrees

Sylwia Cichacz<sup>1</sup>, Agnieszka Görlich<sup>1\*</sup>, Zsolt Tuza<sup>2†</sup>

<sup>1</sup> AGH University of Science and Technology, Al. Mickiewicza 30, 30-059 Kraków, Poland.

<sup>2</sup> Alfréd Rényi Institute of Mathematics, Hungarian Academy of Sciences, P.O.B. 127, H-1364 Budapest, Hungary

**Abstract.** Let  $H = (V, E)$  be a hypergraph with vertex set  $V = \{v_1, \dots, v_n\}$  and edge set  $E = \{e_1, \dots, e_m\}$ . A vertex labeling  $c : V \rightarrow \mathbb{N}$  induces an edge labeling  $c^* : E \rightarrow \mathbb{N}$  by the rule  $c^*(e_i) = \sum_{v_j \in e_i} c(v_j)$ . For integers  $k \geq 2$  we study the existence of labelings satisfying the following condition: Every residue class modulo  $k$  occurs exactly  $\lfloor n/k \rfloor$  or  $\lceil n/k \rceil$  times in the sequence  $c(v_1), \dots, c(v_n)$  and exactly  $\lfloor m/k \rfloor$  or  $\lceil m/k \rceil$  times in the sequence  $c^*(e_1), \dots, c^*(e_m)$ . Hypergraph  $H$  is called  $k$ -cordial if it admits a labeling with these properties.

Hovey [Discrete Math. 93 (1991), 183–194] raised the conjecture (still open for  $k > 5$ ) that if  $H$  is a tree graph, then it is  $k$ -cordial for every  $k$ . Here we investigate the analogous problem for hypertrees (connected hypergraphs without cycles) and present various sufficient conditions on  $H$  to be  $k$ -cordial. From our theorems it follows that every  $k$ -uniform hypertree is  $k$ -cordial, and every hypertree with  $n$  or  $m$  odd is 2-cordial. Both of these results generalize Cahit's theorem [Ars Combin. 23 (1987), 201–207] which states that every tree graph is 2-cordial. We also prove that every uniform hyperpath is  $k$ -cordial for every  $k$ .

**Key words.**  $k$ -cordial graph, hypergraph, hypergraph labeling labeling, hypertree